

Page 8, before line 1, insert the heading - - DETAILED DESCRIPTION OF THE
INVENTION - -

NE Page 15, before line 1, insert the phrase - - "I CLAIM" - -.

Please cancel claims 1-12 without prejudice to or disclaimer of the subject matter recited therein.

IN THE CLAIMS:

Please add new claims 13-25 as follows:

--13. (New) An electrode arrangement for the endocardial discharge of defibrillation pulses in one of the atrium and ventricle of the heart, comprising:

an electrode lead having an undivided proximal end, a distal end and a splitter from which at least two branches of the electrode lead extend to the distal end, each branch having a central core extending from the splitter of the electrode lead, said central core being made of a memory metal structure that enables good contact to be maintained between each branch and a wall of the atrium or the ventricle; and

82 a plurality of electrically conductive surface portions disposed on the at least two branches, said plurality of electrically conductive surface portions being electrically connected by way of the electrode lead to an electrical pulse-discharging device at the proximal end of the electrode lead.

Sub C2 14. (New) The electrode arrangement according to claim 13, further comprising a sliding sleeve displaceable in a longitudinal direction of the electrode lead and actuating means for actuating the sliding sleeve wherein said central core is of one-piece construction in the form of a spring element and causes the branches to split apart when the actuating means moves the

sliding sleeve toward the proximal end of the electrode lead.

Sub C2
15. (New) The electrode arrangement according to claim 13, further comprising a sliding sleeve displaceable in a longitudinal direction of the electrode lead, means for actuating the sliding sleeve to split the at least two branches apart, and means for heating the memory member structure so that the shape of the memory member structure can change to maintain good contact between each branch and a wall of the atrium or the ventricle.

B
16. (New) The electrode arrangement according to claim 15, wherein the memory member structure in at least one of the at least two branches is activatable simultaneously or after the actuating of the sliding sleeve, and a first branch assumes a shape as a septal branch and a second branch assumes a shape as a lateral branch for respectively assuming a septal position and a lateral position in one of the atrium and the ventricle of the heart.

17. (New) The electrode arrangement according to claim 15, wherein at least memory member structure, in at least one of the branches, experiences a predetermined change in shape by being heated above a predetermined temperature.

18. (New) The electrode arrangement according to claim 17, wherein the memory member structure contains titanium.

Sub C3
19. (New) The electrode arrangement according to claim 13, wherein the electrode lead is split into three different branches.

sub
C1
20. (New) The electrode arrangement according to claim 13, wherein the at least two branches include a septal branch and a lateral branch, and the septal branch and lateral branch each have an equal number of electrically conductive surface portions disposed thereon, and each electrically conductive surface portion of the septal branch is unambiguously associated with an electrically conductive surface portion of the lateral branch.

21. (New) The electrode arrangement according to claim 20, wherein the septal and lateral branch each has disposed thereon about 5 to 7 electrically conductive surface portions.

B2
22. (New) The electrode arrangement according to claim 20, wherein the electrically conductive surface portions are in the form of ring electrodes.

23. (New) The electrode arrangement according to claim 21, wherein at least one of the ring electrodes are formed at the tip or distal end of at least one of the at least two branches.

24. (New) The electrode arrangement according to claim 19, wherein the electrically conductive surface portions of each branch are respectively spaced approximately one centimeter from adjacent electrically conductive surface portions.

25. (New) The electrode arrangement according to claim 19, wherein the at least two branches further includes a ventricular branch which is adapted to assume a position in a ventricle of the heart and has at least one ventricle electrode.